# leading Crimping Solutions

扣压解决方案领航者











F51X

### H.C. Material

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden layer

### Heavy-duty Design

Super large opening up to 160mm

Fast working speed & heavy force

Fits in production workshop

### Digital Control

High crimping accuracy within 0.01mm

Easy to understand and operate

### Strong-magnetic Dies

Convenient for assembly and disassembly Crimping neatly and nice

Dies No.	Range	D	L
F32/03*	3.0-5.0	3	35
F32/06	6.0-7.0	6	35
F32/08	8.0-9.0	8	35
F32/10	10.0-11.0	10	35
F32/12	12.0-14.0	12	35
F32/15	15.0-17.0	15	45
F32/18	18.0-20.0	18	45
F32/20	20.0-22.0	20	45
F32/23	23.0-26.0	23	50
F32/26	26.0-31.0	26	65
F32/29	29.0-36.0	29	65
F32/37	37.0-45.0	37	80
F32/46	46.0-54.0	46	80
F32/51	51.0-61.0	51	80
F32/63	63.0-73.0	63	80
F32/70*	70.0-80.0	70	80
* Available with special dies request.			

The HUATAI F51X is perfect for production
crimping in the hardest environments all around
the world. The traditional strong design is ideal
for extreme working conditions for example in
mines or tropical sites.

HUATAI F51X is very easy to operate and offer affordable crimping in service operations. The heavy-duty design of F51X makes it be the best choice of quantity production.

HUATAI F51X				
Forge Steel (Cr40)				
3-80mm (1/8"-3 1/6")				
2", 6SP (ID 51mm)				
+65mm (1")				
160mm (6 5/16")				
160mm (6 5/16")				
90mm (3 1/2")				
31.5Mpa				
3800kN (380T)				
5.5kw				
110V-480V				
Digital				
60dBA				
1200kg				
980*1000*1600mm				

### Standard Accessories

14 sets of Standard Dies

Foot Pedal

Dies Base + QC Tool

Spare-parts Packet

### **Optional Accessories**

**Back Stop Device** 

**Customized Dies** 

Mirror











**F32D** 

Н	_					-
	100	m v.	1	- 1	7	7 /

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden laver

### **Compact Design**

Pipeless hydraulic valve-block connection

Stable pressure conduction

Fits in any workshop

### Digital Control

High crimping accuracy within 0.01mm

Easy to understand and operate

### Strong-magnetic Dies

Convenient for assembly and disassembly Crimping neatly and nice

Dies No.	Range	D	L
F32/03*	3.0-5.0	3	35
F32/06	6.0-7.0	6	35
F32/08	8.0-9.0	8	35
F32/10	10.0-11.0	10	35
F32/12	12.0-14.0	12	35
F32/15	15.0-17.0	15	45
F32/18	18.0-20.0	18	45
F32/20	20.0-22.0	20	45
F32/23	23.0-26.0	23	50
F32/26	26.0-31.0	26	65
F32/29	29.0-36.0	29	65
F32/37	37.0-45.0	37	80
F32/46	46.0-54.0	46	80
F32/51	51.0-61.0	51	80
F32/63	63.0-73.0	63	80
F32/70*	70.0-80.0	70	80
* Available w	vith special die	s requ	est.

The HUATAI F32D is perfect for service crimping in the hardest environments all around the world. The traditional strong design is ideal for extreme working conditions for example in mines or tropical sites.

HUATAI F32D is very easy to operate and offer affordable crimping in service operations. The compact design of HUATAI F32D means it is easily movable to anywhere.

HUATAI F32D			
H.C. Material	Forge Steel (Cr40)		
Crimping Range	3-80mm (1/8"-3 1/6")		
Max. Hydraulic Hose	2", 4SP (ID 51mm)		
Max. Opening	+25mm (1")		
Opening without Dies	118mm (4 5/8")		
Accessible Diameter	118mm (4 5/8")		
Master Die Length	80mm (3 1/6")		
System Pressure	31.5Mpa		
Max. Crimping Force	3600kN (360T)		
Motor Power	4kw		
Standard Voltage	110V-480V		
Control	Digital		
Noise Level	60dBA		
Weight	260kg		
LxWxH	620*500*720mm		

### Standard Accessories

14 sets of Standard Dies

Foot Pedal

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

Dies Base + Power QC Tool

**Customized Dies** 











ground, and no need for an extra work bench, this ergonomic design enable crimping works more conveniently. The built-in motor of HUATAI F51N reduces

The HUATAI F51N can operate on the

The built-in motor of HUATAI F51N reduces most of the noise, and its built-in rack saves much space, this two points make HUATAI F51N become the best choice of production workshop.

## **F51N**

Ľ	H.C. Material
1	Made of Cr40 forge steel
1	More than 6 months aging treatment
-	2mm thick harden layer
	Cabinet Design
1	No need extra workbench
5	Soft noise
F	Fits in production workshop
	Digital Control
ŀ	High crimping accuracy within 0.01mm
E	Easy to understand and operate
	Strong-magnetic Dies
(	Convenient for assembly and disassembly
(	Crimping neatly and nice

Dies No.	Range	D	L
F32/03*	3.0-5.0	3	35
F32/06	6.0-7.0	6	35
F32/08	8.0-9.0	8	35
F32/10	10.0-11.0	10	35
F32/12	12.0-14.0	12	35
F32/15	15.0-17.0	15	45
F32/18	18.0-20.0	18	45
F32/20	20.0-22.0	20	45
F32/23	23.0-26.0	23	50
F32/26	26.0-31.0	26	65
F32/29	29.0-36.0	29	65
F32/37	37.0-45.0	37	80
F32/46	46.0-54.0	46	80
F32/51	51.0-61.0	51	80
F32/63	63.0-73.0	63	80
F32/70*	70.0-80.0	70	80
* Available w	rith special die	s requ	est.

HUATAI F51N				
H.C. Material	Forge Steel (Cr40)			
Crimping Range	3-80mm (1/8"-3 1/6")			
Max. Hydraulic Hose	2", 4SP (ID 51mm)			
Max. Opening	+25mm (1")			
Opening without Dies	118mm (4 5/8")			
Accessible Diameter	118mm (4 5/8")			
Master Die Length	80mm (3 1/6")			
System Pressure	31.5Mpa			
Max. Crimping Force	3600kN (360T)			
Motor Power	4kw			
Standard Voltage	110V-480V			
Control	Digital			
Noise Level	60dBA			
Weight	290kg			
LxWxH	920*510*1140mm			

Standard Accessories
14 sets of Standard Dies
Foot Pedal
Spare-parts Packet

### **Optional Accessories**

Dies Rack + Power QC Tool

Dies Drawer

Customized Dies











HUATAI FC51S cutting machine is automatic operated and offers quick and precise cutting for all types of hoses, it is designed for service use in production workshop.

HUATAI FC51S offers safe cutting with protected blade and safety shield. The hose is pushed against the blade by pneumatic spindle, it is easy and simple to use, and it can be used for cutting up to 2" braided hoses efficiently, fast and safely.

### Aluminum Shell Motor

Better heat dissipation

Soft noise

Stable performance

### Compact Design

Light weight & small volume

Fits in any workshop

### Pneumatic Automatic

Efficiently & Safely

Low noise & less smoke

HUATAI FC51S		
Hose Capacity	2", 4SP (ID 51mm)	
Motor Power	3kw	
Standard Voltage	110V-480V	
Blade Diameter	350*2.8*32mm	
Speed of Blade	2880rpm	
Control	Automatic	
Noise Level	60dBA	
Weight	80kg	
LxWxH	700*600*450mm	

### **Standard Accessories**

Smooth Blade

Foot Pedal

### **Optional Accessories**

**Toothed Blades** Smooth Blades **Working Table** 















**F20V** 

H.(	-	1 V I	7	_	-	
	-	111	0 1 11	_J #	[0]	

Made of Cr40 forge steel has com

More than 6 months aging treatment

2mm thick harden layer

### Compact Design

Pipeless hydraulic valve-block connection

Stable pressure conduction

Fits in repair workshop

### **Battery Powered**

12V or 24V battery powered

Apply to mobile van or field service

### Strong-magnetic Dies

Convenient for assembly and disassembly

www.hthydraulies.com www.hthydraulies.com

Crimping neatly and nice

Dies No.	Range	D	L
F20/03*	3.0-5.0	3	35
F20/06*	6.0-7.0	6	35
F20/08*	8.0-9.0	8	35
F20/10*	10.0-11.0	10	35
F20/12*	12.0-14.0	12	35
F20/15	15.0-17.0	15	65
F20/18	18.0-20.0	18	65
F20/20	20.0-22.0	20	65
F20/23	23.0-26.0	23	65
F20/26	26.0-31.0	26	65
F20/29	29.0-36.0	29	65
F20/37	37.0-45.0	37	70
F20/46	46.0-54.0	46	70
F20/51*	51.0-61.0	51	70
* Available w	ith special die	s reque	st.

HUATAI F20V crimping machine is designed for field service when repairs must be made on-site, it is simple and compact in construction, easy to operate.

HUATAI F20V is battery powered with 12V or 24V, provides 2600kN crimping force in a highly compact, ergonomic design. Portability and usefulness for service vehicles in various industries make them ideal for field service and emergency repairs.

 	A		-		а
		1		OV	

H.C. Material	Forge Steel (Cr40)
Crimping Range	3-61mm (1/8"-2 3/8")
Max. Hydraulic Hose	1 1/2", 4SP (ID 38mm)
Max. Opening	+21mm (5/6")
Opening without Dies	96mm (3 4/5")
Accessible Diameter	90mm (3 1/2")
Master Die Length	70mm (2 3/4")
System Pressure	31.5Mpa
Max. Crimping Force	2600kN (260T)
Motor Power	3kw
Standard Voltage	12V/24V
Control	Automatic
Noise Level	60dBA
Weight	135kg
LxWxH	650*300*500mm

### Standard Accessories

8 sets of Standard Dies

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

**Customized Dies** 











**F20D** 

	~	TV7		9	щ	II)		п
Н.(		VI	-1	۸	3	pl.l.	-	

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden laver

### **Compact Design**

Pipeless hydraulic valve-block connection

Stable pressure conduction

Fits in any workshop

### Digital Control

High crimping accuracy within 0.01mm

Easy to understand and operate

### Strong-magnetic Dies

Convenient for assembly and disassembly Crimping neatly and nice

Dies No.	Range	D	L
F20/03*	3.0-5.0	3	35
F20/06	6.0-7.0	6	35
F20/08	8.0-9.0	8	35
F20/10	10.0-11.0	10	35
F20/12	12.0-14.0	12	35
F20/15	15.0-17.0	15	65
F20/18	18.0-20.0	18	65
F20/20	20.0-22.0	20	65
F20/23	23.0-26.0	23	65
F20/26	26.0-31.0	26	65
F20/29	29.0-36.0	29	65
F20/37	37.0-45.0	37	70
F20/46	46.0-54.0	46	70
F20/51*	51.0-61.0	51	70
* Available w	rith special die	s reque	est.

Available with special dies request.

The HUATAI F20D is perfect for service crimping in the hardest environments all around the world. The traditional strong design is ideal for extreme working conditions for example in mines or tropical sites.

HUATAI F20D is very easy to operate and offer affordable crimping in service operations. The compact design of HUATAI F20D means it is easily movable to anywhere.

	HUATAI F20D						
j	H.C. Material	Forge Steel (Cr40)					
-	Crimping Range	3-61mm (1/8"-2 3/8")					
	Max. Hydraulic Hose	1 1/2", 4SP (ID 38mm)					
	Max. Opening	+21mm (5/6")					
	Opening without Dies	96mm (3 4/5")					
	Accessible Diameter	90mm (3 1/2")					
	Master Die Length	70mm (2 3/4")					
	System Pressure	31.5Mpa					
	Max. Crimping Force	3200kN (320T)					
y	Motor Power	4kw					
	Standard Voltage	110V-480V					
	Control	Digital					
T	Noise Level	65dBA					
	Weight	200kg					
	LxWxH	600*480*650mm					

### Standard Accessories

12 sets of Standard Dies

Foot Pedal

Dies Drawer

Spare-parts Packet

**Optional Accessories** 

**Customized Dies** 







The HUATAI F32D is perfect for service
crimping in the hardest environments all around
the world. The traditional strong design is ideal
for extreme working conditions for example in
mines or tropical sites.

HUATAI F32D is very easy to operate and offer affordable crimping in service operations. The compact design of HUATAI F32D means it is easily movable to anywhere.

	HUAT	AI F32D
	H.C. Material	Forge Steel (Cr40)
	Crimping Range	3-80mm (1/8"-3 1/6")
	Max. Hydraulic Hose	2", 4SP (ID 51mm)
o I	Max. Opening	+25mm (1")
	Opening without Dies	118mm (4 5/8")
	Accessible Diameter	118mm (4 5/8")
	Master Die Length	80mm (3 1/6")
	System Pressure	31.5Mpa
	Max. Crimping Force	3600kN (360T)
	Motor Power	4kw
	Standard Voltage	110V-480V
	Control	Digital
	Noise Level	65dBA
	Weight	230kg
	LxWxH	600*480*700mm

### H.C. Material

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden layer

### Compact Design

Pipeless hydraulic valve-block connection Stable pressure conduction

Fits in any workshop

### Digital Control

High crimping accuracy within 0.01mm

Easy to understand and operate

### Strong-magnetic Dies

Convenient for assembly and disassembly Crimping neatly and nice

Range	D	L
3.0-5.0	3	35
6.0-7.0	6	35
8.0-9.0	8	35
10.0-11.0	10	35
12.0-14.0	12	35
15.0-17.0	15	45
18.0-20.0	18	45
20.0-22.0	20	45
23.0-26.0	23	50
26.0-31.0	26	65
29.0-36.0	29	65
37.0-45.0	37	80
46.0-54.0	46	80
51.0-61.0	51	80
63.0-73.0	63	80
70.0-80.0	70	80
	3.0-5.0 6.0-7.0 8.0-9.0 10.0-11.0 12.0-14.0 15.0-17.0 18.0-20.0 20.0-22.0 23.0-26.0 26.0-31.0 29.0-36.0 37.0-45.0 46.0-54.0 51.0-61.0 63.0-73.0	3.0-5.0 3 6.0-7.0 6 8.0-9.0 8 10.0-11.0 10 12.0-14.0 12 15.0-17.0 15 18.0-20.0 18 20.0-22.0 20 23.0-26.0 23 26.0-31.0 26 29.0-36.0 29 37.0-45.0 37 46.0-54.0 46 51.0-61.0 51 63.0-73.0 63

### Standard Accessories

14 sets of Standard Dies

Foot Pedal

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

Dies Base + Power QC Tool

**Customized Dies** 











F20

		_			
	40.00	1 V I		7-1	ial
= 5	-	11/11	0 1	11 -1 11	11011

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden laver

### Compact Design

Pipeless hydraulic valve-block connection

Stable pressure conduction

Fits in any workshop

### Full/semi Automatic

Semi-auto mode achieve accurate crimps

Full-auto mode enable batch crimps

### Strong-magnetic Dies

Convenient for assembly and disassembly Crimping neatly and nice

Dies No.	Range	D	L
F20/03*	3.0-5.0	3	35
F20/06	6.0-7.0	6	35
F20/08	8.0-9.0	8	35
F20/10	10.0-11.0	10	35
F20/12	12.0-14.0	12	35
F20/15	15.0-17.0	15	65
F20/18	18.0-20.0	18	65
F20/20	20.0-22.0	20	65
F20/23	23.0-26.0	23	65
F20/26	26.0-31.0	26	65
F20/29	29.0-36.0	29	65
F20/37	37.0-45.0	37	70
F20/46	46.0-54.0	46	70
F20/51*	51.0-61.0	51	70
Available w	ith special die	s requ	est.

The HUATAI F20 is perfect for service crimping in the hardest environments all around the world. The traditional strong design is ideal for extreme working conditions for example in mines or tropical sites.

HUATAI F20 is very easy to operate and offer affordable crimping in service operations. The compact design of HUATAI F20 means it is easily movable to anywhere.

HUATAI F20					
H.C. Material	Forge Steel (Cr40)				
Crimping Range	3-61mm (1/8"-2 3/8")				
Max. Hydraulic Hose	1 1/2", 4SP (ID 38mm)				
Max. Opening	+21mm (5/6")				
Opening without Dies	96mm (3 4/5")				
Accessible Diameter	90mm (3 1/2")				
Master Die Length	70mm (2 3/4")				
System Pressure	31.5Mpa				
Max. Crimping Force	3200kN (320T)				
Motor Power	4kw				
Standard Voltage	110V-480V				
Control	Full/semi Automatic				
Noise Level	65dBA				
Weight	200kg				
LxWxH	600*480*650mm				

### Standard Accessories

12 sets of Standard Dies

Foot Pedal

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

**Customized Dies** 







The HUATAI F32 is perfect for service crimping in the hardest environments all around the world. The traditional strong design is ideal for extreme working conditions for example in mines or tropical sites.

HUATAI F32 is very easy to operate and offer affordable crimping in service operations. The compact design of HUATAI F32 means it is easily movable to anywhere.

HUATAI F32			
H.C. Material	Forge Steel (Cr40)		
Crimping Range	3-80mm (1/8"-3 1/6")		
Max. Hydraulic Hose	2", 4SP (ID 51mm)		
Max. Opening	+25mm (1")		
Opening without Dies	118mm (4 5/8")		
Accessible Diameter	118mm (4 5/8")		
Master Die Length	80mm (3 1/6")		
System Pressure	31.5Mpa		
Max. Crimping Force	3600kN (360T)		
Motor Power	4kw		
Standard Voltage	110V-480V		
Control	Full/semi Automatic		
Noise Level	65dBA		
Weight	230kg		
LxWxH	600*480*700mm		

### H.C. Material

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden layer

### **Compact Design**

Pipeless hydraulic valve-block connection
Stable pressure conduction

Fits in any workshop

### Full/semi Automatic

Semi-auto mode achieve accurate crimps

Full-auto mode enable batch crimps

### Strong-magnetic Dies

Convenient for assembly and disassembly
Crimping neatly and nice

Range	D	L
3.0-5.0	3	35
6.0-7.0	6	35
8.0-9.0	8	35
10.0-11.0	10	35
12.0-14.0	12	35
15.0-17.0	15	45
18.0-20.0	18	45
20.0-22.0	20	45
23.0-26.0	23	50
26.0-31.0	26	65
29.0-36.0	29	65
37.0-45.0	37	80
46.0-54.0	46	80
51.0-61.0	51	80
63.0-73.0	63	80
70.0-80.0	70	80
	3.0-5.0 6.0-7.0 8.0-9.0 10.0-11.0 12.0-14.0 15.0-17.0 18.0-20.0 20.0-22.0 23.0-26.0 26.0-31.0 29.0-36.0 37.0-45.0 46.0-54.0 51.0-61.0 63.0-73.0 70.0-80.0	3.0-5.0 3 6.0-7.0 6 8.0-9.0 8 10.0-11.0 10 12.0-14.0 12 15.0-17.0 15 18.0-20.0 18 20.0-22.0 20 23.0-26.0 23 26.0-31.0 26 29.0-36.0 29 37.0-45.0 37 46.0-54.0 46 51.0-61.0 51 63.0-73.0 63

## 14 sets of Standard Dies

Foot Pedal

Standard Accessories

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

Dies Base + Power QC Tool

**Customized Dies** 











easy to operate. HUATAI F20V is battery powered with 12V or 24V, provides 2600kN crimping force in a highly compact, ergonomic design. Portability and usefulness for service vehicles in various industries make them ideal for field service and

emergency repairs.

LxWxH

## **F20V**

n.c. Material	
Made of Cr40 forge steel	
More than 6 months aging treatm	ment
2mm thick harden layer	
Compact Design	
Pipeless hydraulic valve-block co	nnection
Stable pressure conduction	
Fits in repair workshop	chthyara
Battery Powered	
12V or 24V battery powered	
Apply to mobile van or field servi	ice
Strong-magnetic Dies	
Convenient for assembly and dis	assembly

Crimping neatly and nice

Dies No.	Range	D	L	
F20/03*	3.0-5.0	3	35	
F20/06*	6.0-7.0	6	35	
F20/08*	8.0-9.0	8	35	
F20/10*	10.0-11.0	10	35	
F20/12*	12.0-14.0	12	35	
F20/15	15.0-17.0	15	65	
F20/18	18.0-20.0	18	65	
F20/20	20.0-22.0	20	65	
F20/23	23.0-26.0	23	65	
F20/26	26.0-31.0	26	65	
F20/29	29.0-36.0	29	65	
F20/37	37.0-45.0	37	70	
F20/46	46.0-54.0	46	70	
F20/51*	51.0-61.0	51	70	
Available w	ith special dies	reques	st.	

HUATAI F20V				
H.C. Material	Forge Steel (Cr40)			
Crimping Range	3-61mm (1/8"-2 3/8")			
Max. Hydraulic Hose	1 1/2", 4SP (ID 38mm)			
Max. Opening	+21mm (5/6")			
Opening without Dies	96mm (3 4/5")			
Accessible Diameter	90mm (3 1/2")			
Master Die Length	70mm (2 3/4")			
System Pressure	31.5Mpa			
Max. Crimping Force	2600kN (260T)			
Motor Power	3kw			
Standard Voltage	12V/24V			
Control	Automatic			
Noise Level	65dBA			
Weight	135kg			

### Standard Accessories

550\*280\*550mm

8 sets of Standard Dies

Dies Drawer

Spare-parts Packet

**Customized Dies** Manual QC Tool











## **F32V**

_		m				
H	-	u v	_	7.3	7	7.6
I = PI	O'P'	111	I o b	# C.J.	of [ 0	7.00

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden layer

### Compact Design

Pipeless hydraulic valve-block connection

Stable pressure conduction

Fits in repair workshop

### **Battery Powered**

12V or 24V battery powered

Apply to mobile van or field service

### Strong-magnetic Dies

Convenient for assembly and disassembly

Crimping neatly and nice

Dies No.	Range	D	L
F32/03*	3.0-5.0	3	35
F32/06*	6.0-7.0	6	35
F32/08*	8.0-9.0	8	35
F32/10*	10.0-11.0	10	35
F32/12*	12.0-14.0	12	35
F32/15	15.0-17.0	15	45
F32/18	18.0-20.0	18	45
F32/20	20.0-22.0	20	45
F32/23	23.0-26.0	23	50
F32/26	26.0-31.0	26	65
F32/29	29.0-36.0	29	65
F32/37	37.0-45.0	37	80
F32/46	46.0-54.0	46	80
F32/51	51.0-61.0	51	80
F32/63	63.0-73.0	63	80
F32/70*	70.0-80.0	70	80
* Available w	vith special die	s requ	est.

HUATAI F32V crimping machine is designed for field service when repairs must be made on-site, it is simple and compact in construction, easy to operate.

HUATAI F32V is battery powered with 12V or 24V, provides 2800kN crimping force in a highly compact, ergonomic design. Portability and usefulness for service vehicles in various industries make them ideal for field service and emergency repairs.

HOATAITSEV		
Material	Forge Steel (Cr40)	
oing Range	3-80mm (1/8"-3 1/6")	

H.C.

Crimp

Motor Power

LIIATAI E22V

Max. Hydraulic Hose 2", 4SP (ID 51mm)

Max. Opening +25mm (1")

Opening without Dies 118mm (4 5/8")
Accessible Diameter 118mm (4 5/8")

Master Die Length 80mm (3 1/6")

System Pressure 31.5Mpa

Max. Crimping Force 2800kN (280T)

3kw

Standard Voltage 12V/24V

Control Automatic

Noise Level 65dBA

Weight 150kg

L x W x H 600\*300\*580mm

### **Standard Accessories**

10 sets of Standard Dies

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

**Customized Dies** 











**F20M** 

 Se 17	F I I .	. 1 . 1	
		J H I H I I	

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden laver

### Compact Design

Pipeless hydraulic valve-block connection

Stable pressure conduction

Fits in repair workshop

### **Manual Operation**

No electricity/compressed air requested

Apply to mobile van or field service

### Strong-magnetic Dies

Convenient for assembly and disassembly Crimping neatly and nice

Dies No.	Range	D	L
F20/03*	3.0-5.0	3	35
F20/06*	6.0-7.0	6	35
F20/08*	8.0-9.0	8	35
F20/10*	10.0-11.0	10	35
F20/12*	12.0-14.0	12	35
F20/15	15.0-17.0	15	65
F20/18	18.0-20.0	18	65
F20/20	20.0-22.0	20	65
F20/23	23.0-26.0	23	65
F20/26	26.0-31.0	26	65
F20/29	29.0-36.0	29	65
F20/37	37.0-45.0	37	70
F20/46	46.0-54.0	46	70
F20/51*	51.0-61.0	51	70
Available w	ith special die	s requ	est.

HUATAI F20M is a manually operated hydraulic crimping machine for repair workshop. This hand-operated movable crimper works even in places where electricity or compressed air are not available.

HUATAI F20M is simple in construction, easy to operate, and highly reliable. Its ergonomic design, efficient, fast pump and impressively high crimping force makes it ideal crimper for field service.

H.C. Material	Forge Steel (Cr40)
Crimping Range	3-61mm (1/8"-2 3/8")
Max. Hydraulic Hose	1 1/2", 4SP (ID 38mm)
Max. Opening	+21mm (5/6")
Opening without Dies	96mm (3 4/5")
Accessible Diameter	90mm (3 1/2")
Master Die Length	70mm (2 3/4")
System Pressure	31.5Mpa
Max. Crimping Force	2300kN (230T)
Motor Power	Hand Pump
Standard Voltage	None
Control	Manual
Noise Level	None
Weight	135kg
LxWxH	550*280*550mm

### Standard Accessories

8 sets of Standard Dies

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

**Customized Dies** 











**F32M** 

H.C		

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden layer

### Compact Design

Pipeless hydraulic valve-block connection

Stable pressure conduction

Fits in repair workshop

### **Manual Operation**

No electricity/compressed air requested

Apply to mobile van or field service

### Strong-magnetic Dies

Convenient for assembly and disassembly

Crimping neatly and nice

Dies No.	Range	D	L
F32/03*	3.0-5.0	3	35
F32/06*	6.0-7.0	6	35
F32/08*	8.0-9.0	8	35
F32/10*	10.0-11.0	10	35
F32/12*	12.0-14.0	12	35
F32/15	15.0-17.0	15	45
F32/18	18.0-20.0	18	45
F32/20	20.0-22.0	20	45
F32/23	23.0-26.0	23	50
F32/26	26.0-31.0	26	65
F32/29	29.0-36.0	29	65
F32/37	37.0-45.0	37	80
F32/46	46.0-54.0	46	80
F32/51	51.0-61.0	51	80
F32/63	63.0-73.0	63	80
F32/70*	70.0-80.0	70	80
* Available w	rith special die	s requ	est.

HUATAI F32M is a manually operated hydraulic crimping machine for repair workshop. This hand-operated movable crimper works even in places where electricity or compressed air are not available.

HUATAI F32M is simple in construction, easy to operate, and highly reliable. Its

ergonomic design, efficient, fast pump and impressively high crimping force makes it ideal crimper for field service.

HUATAI F32M				
H.C. Material	Forge Steel (Cr40)			
Crimping Range	3-80mm (1/8"-3 1/6")			
Max. Hydraulic Hose	2", 4SP (ID 51mm)			
Max. Opening	+25mm (1")			
Opening without Dies	118mm (4 5/8")			
Accessible Diameter	118mm (4 5/8")			
Master Die Length	80mm (3 1/6")			
System Pressure	31.5Mpa			
Max. Crimping Force	2600kN (260T)			
Motor Power	Hand Pump			
Standard Voltage	None			
Control	Manual			
Noise Level	None			
Weight	150kg			
LxWxH	600*300*580mm			

### Standard Accessories

10 sets of Standard Dies

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

**Customized Dies** 











F16HP

### H.C. Material

Made of Cr40 forge steel

More than 6 months aging treatment

2mm thick harden laver

### Compact Design

Light and compact in size

Easy to carry to any location

Fits in repair workshop

### **Manual Operation**

No electricity/compressed air requested

Apply to mobile van or field service

### Strong-magnetic Dies

Convenient for assembly and disassembly Crimping neatly and nice

Dies No.	Range	D	L	
F16/03*	3.0-5.0	3	35	
F16/06*	6.0-7.0	6	35	
F16/08*	8.0-9.0	8	35	
F16/10*	10.0-11.0	10	35	
F16/12*	12.0-14.0	12	35	
F16/15	15.0-17.0	15	65	
F16/18	18.0-20.0	18	65	
F16/20	20.0-22.0	20	65	
F16/23	23.0-26.0	23	65	
F16/26	26.0-31.0	26	65	
F16/29	29.0-36.0	29	65	
F16/37	37.0-45.0	37	65	
* Available w	ith special die	s requ	est.	

HUATAI F16HP is a manually operated hydraulic crimping machine for repair workshop. This hand-operated portable crimper works even in places where electricity or compressed air are not available.

HUATAI F16HP is simple in construction, easy to operate, and highly reliable. Its ergonomic design, efficient, fast pump and impressively high crimping force makes it ideal crimper for field service.

HU	AT	AI	FI	6H	P
----	----	----	----	----	---

ч	4110111	
	H.C. Material	Forge Steel (Cr40)
	Crimping Range	3-45mm (1/8"-1 3/4")
П	Max. Hydraulic Hose	1", 2SN (ID 25mm)
	Max. Opening	+20mm (4/5")
	Opening without Dies	55mm (2 1/6")
	Accessible Diameter	55mm (2 1/6")
	Master Die Length	65mm (2 1/2")
	System Pressure	31.5Mpa
	Max. Crimping Force	995kN (95.5T)
	Motor Power	Hand Pump
T	Standard Voltage	None
	Control	Manual
	Noise Level	None
У	Weight	24.5kg
	LxWxH	320*350*290mm

### Standard Accessories

7 sets of Standard Dies

Dies Drawer

Spare-parts Packet

### **Optional Accessories**

**Customized Dies** 









HUATAI FC51 cutting machine is manually operated and designed for service use in workshop. It is easy and simple to use, and it can be used for cutting up to 2" braided hoses efficiently, fast and safely.

## FC51

### Aluminum Shell Motor

Better heat dissipation

Soft noise

Stable performance

### Compact Design

Light weight & small volume

Fits in any workshop anthydraulics com

### Smooth Blade

Neat cut surface

Low noise & less smoke

### **Standard Accessories**

Smooth Blade

**Cutting Handle** 

**Toothed Blades** 

**Smooth Blades** 

**Working Table** 



HUATAI FC51		
Hose Capacity	2", 4SP (ID 51mm)	
Motor Power	3kw	
Standard Voltage	110V-480V	
Blade Diameter	350*2.8*32mm	
Speed of Blade	2880rpm	
Control	Hand Operation	
Noise Level	65dBA	
Weight	70kg	
LxWxH	650*600*580mm	













HUATAI FC51V cutting machine is manually operated and designed for field service when repairs must be made on-site.

HUATAI FC51V is battery powered with 12V or 24V. It is easy and simple to use, and it can be used for cutting up to 2" braided hoses efficiently, fast and safely.



### **Battery Powered**

12V or 24V battery powered

Apply to mobile van or field service

### Compact Design

Light weight & small volume

Fits in repair workshop

### Smooth Blade

Neat cut surface

Low noise & less smoke

### **Standard Accessories**

Smooth Blade

**Cutting Handle** 

### **Optional Accessories**

**Toothed Blades Smooth Blades** 



HUATAI FC51V		
Hose Capacity	2", 4SP (ID 51mm)	
Motor Power	3kw	
Standard Voltage	12V/24V	
Blade Diameter	350*2.8*32mm	
Speed of Blade	2500rpm	
Control	Hand Operation	
Noise Level	65dBA	
Weight	60kg	
LxWxH	650*600*580mm	













HUATAI FS51 skiving machine with a foot pedal is suitable for skiving external and internal hydraulic hoses from dimensions 1/4" to 2". HUATAI FS51 is ergonimically designed for efficiency and ease of use. It has adjustable tool operation, which saves in tool costs, and maximizes productivity.



### Special Motor

Aluminum shell motor

Reducing gear attached

Soft noise

### Compact Design

Light weight & small volume

Fits in any workshop

### Protection Cover

Poweroff protection

Visible operation

### **Standard Accessories**

Foot Pedal

**External Mandrels** 

### **Optional Accessories**

Internal Mandrels

**Working Table** 



HUATAI FS51		
Hose Capacity	2", 4SP (ID 51mm)	
Motor Power	0.75kw	
Standard Voltage	110V-480V	
Mandrel Tools	10pcs	
Speed of Tool Rotation	100r/min	
Control	Foot Operation	
Noise Level	60dBA	
Weight	45kg	
LxWxH	600*400*370mm	
	THE STEP IN	













HUATAI FI51 is an integrated cutting and skiving machine for hydraulic hose. It is easy and simple to use, it can be used for cutting and skiving up to 2" braided hoses efficiently, fast and safely.

The compact design of HUATAI FI51 makes it save much space and fits in any workshop. Its skiving part has adjustable tool operation, which saves in tool costs, and maximizes productivity; the cutting part is manually operated and equipped with high-speed steel blade.

Aluminum Shell Motor
Better heat dissipation
Soft noise
Stable performance www.hthydraul
Integrated Design
Light weight & small volume
Compact, fits in any workshop
Smooth Blade
Neat cut surface
Low noise & Jess smoke

draulics.com www.hthydrau

Stand	ard	Acc	2550	ries

Smooth Blade
Cutting Handle
External Mandrels

### **Optional Accessories**

Smooth Blades
Internal Mandrels
Working Table

HUATAI FI51		
2", 4SP (ID 51mm)		
3kw		
110V-480V		
350*2.8*32mm		
2880rpm		
Hand Operation		
65dBA		
110kg		
1000*600*580mm		







Jingxian Huatai Hydraulic Rubber Co., Ltd
Erzhong North Road, West Industrial Zone, Jingxian, Hengshui, Hebei, China
Tel: +86-534-2302929 Fax: +86-534-2302525